



Control4 Navigators allow you to interact with your Control4® system. Control your lights, temperature, movies, music and more from any of our intuitive interfaces.

You can interact with Control4® Navigators in a variety of ways:

- **On Screen** – Using your Control4® System Remote Control, enjoy total home control from any television in your home.
- **Touch Screen** – Control4 offers a variety of Touch Screens that give you total home control from convenient locations throughout your home.
- **Mobile** – Using the Control4 My Home application from the iTunes App Store, you can enjoy total home control from your iPhone, iPod Touch, or iPad
- **System Remote Control** – The System Remote Control SR-250 has a convenient OLED backlit display that converts the Control4 Navigator into a text format.
- **Keypads** – Unlock the power of customizable, preset, one-touch control functionality with our elegant Keypads.

It is all part of the Control4 vision. We bring the benefits of a truly automated home to more people with solutions that are affordable, easy to install and designed to adapt to any home or lifestyle.

Features & Benefits

- **Intelligent Design** – Enjoy intuitive home control with any of our easy-to-use interfaces.
- **Incredible Value** – Get the elegance of high-quality, total home control at an affordable price.
- **Modular Solution** – Expand your system to include in-wall, portable, tabletop or mobile user interfaces to create the perfect control experience.
- **Retrofittable** – Choose a wired or wireless user-interface solution that fits your needs, whether you have a new or existing home.
- **4Sight Remote Management** – Enjoy total home control from anywhere in the world with an Internet connection.*

*Remote Access Requires Subscription to 4Sight

Touch Screens



Control4® Portable Touch Screen (7")

Control4® Portable Touch Screens are the most flexible way to enjoy total home control. Browse your music and videos anywhere from your porch to your couch.



Control4® InfinityEdge™ In-Wall Touch Screen (5", 7")

Control4® In-Wall Touch Screens are a stylish way to add total-home control that's always there when you need it. These Ethernet/WiFi Touch Screens are ideal for areas of your home such as the kitchen or living room, where convenient system monitoring and control are important.



Control4® Table Top Touch Screen (3.8", 7")

Control4® Table Top Touch Screens provide the convenience of total home control when in-wall installation isn't practical. These Ethernet/WiFi Touch Screens are ideal for counters, nightstands and tables.



Control4® My Home App*

The Control4® My Home App available from the iTunes app store allows you to experience the convenience of using your iPhone, iPod Touch, or iPad to control your home with the same, familiar Control4 navigation.

*Mobile Navigator License required for activation.

Touch Screens

	In Wall				Portable	Table Top
	Control4® 7" In-Wall Touch Screen	Control4® 10.5" In-Wall Touch Screen	Control4® InfinityEdge™ 5" In-Wall Touch Screen	Control4® InfinityEdge™ 7" In-Wall Touch Screen	Control4® 7" WiFi Portable Touch Screen	Control4® 7" Table Top Touch Screen
Model Number	C4-TSWM7-E-B	C4-TSWM10-E-X	C4-TSWMCS5-EG-BL, C4-TSWMCS5-EG-WH	C4-TSWM7-EG-BL, C4-TSWM7-EG-WH-2	C4-TSM7-G-B	C4-TSTR7-EG-B
Display						
Diagonal Display Area	7.0"	10.5"	4.7"	7.0"	7.0"	7.0"
Pixel Resolution	800 x 480	800 x 600	800 x 480	800 x 480	800 x 480	800 x 480
Color Depth	24-bit	18-bit	24-bit	24-bit	24-bit	24-bit
Communications						
WiFi	802.11 b/g	802.11 b/g	802.11 b/g	802.11 b/g	802.11 b/g	802.11 b/g
Security	WPA/WPA2 (PSK) WEP-64 WEP-128	WEP	WPA/WPA2 (PSK) WEP-64 WEP-128	WPA/WPA2 (PSK) WEP-64 WEP-128	WPA/WPA2 (PSK) WEP-64 WEP-128	WPA/WPA2 (PSK) WEP-64 WEP-128
Ethernet	10/100	10/100	10/100	10/100	N/A	10/100
Power Requirements						
Power Supply	100-240 VAC, 50-60 Hz	10-18 VDC, 3 Amps	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz
Power over Ethernet (PoE) Support	Yes	N/A	Yes	Yes	N/A	Yes
Battery Life	N/A	N/A	N/A	N/A	6 hours	N/A
Standby Battery Life	N/A	N/A	N/A	N/A	24 hours	N/A
Inputs/Outputs						
Audio Output	1 (RCA)	N/A	N/A	N/A	1 (3.5 mm)	1 (RCA)
Sensors						
Wake On Motion Sensor	N/A	N/A	N/A	N/A	Yes	N/A
Ambient Light Sensor	Yes	N/A	N/A	N/A	N/A	Yes
Proximity Sensor	Yes	N/A	N/A	N/A	N/A	Yes
Environmental						
Operational	32° F - 104° F (0° C - 40° C)	32° F - 122° F (0° C - 50° C)	32° F - 104° F (0° C - 40° C)	32° F - 104° F (0° C - 40° C)	32° F - 104° F (0° C - 40° C)	32° F - 104° F (0° C - 40° C)
Humidity	5% - 90% Non-Condensing	5% - 90% Non-Condensing	5% - 90% Non-Condensing	5% - 90% Non-Condensing	5% - 90% Non-Condensing	5% - 90% Non-Condensing
Storage	-4 F - 140 F (-20 C to 60 C)	-4 F - 140 F (-20 C to 60 C)	-4 F - 140 F (-20 C to 60 C)	-4 F - 140 F (-20 C to 60 C)	-4 F - 140 F (-20 C to 60 C)	-4 F - 140 F (-20 C to 60 C)
Dimensions						
W x H x D	8.1" x 6.0" x 3.4" (207mm x 153mm x 87mm)	9.6" x 12.6" x 2" (245mm x 321mm x 51mm)	3.15" x 0.8" x 4.8" (80mm x 21mm x 122mm)	4.6" x 0.9" x 6.0" (110mm x 23mm x 175mm)	5" x 9.5" x 1.4" (127mm x 241mm x 36mm)	10.5" x 9.4" x 5.6 (267mm x 238mm x 143mm)
Weight	1.6 lbs (0.73 kg)	4.5 lbs (2.04 kg)	1.0 lbs (0.45 kg)	1.55 lbs (0.70 kg)	3.4 lbs (1.54 kg)	3.45 lbs (1.56 kg)

120V Keypads



Control4® 120V & 240V Keypads

The Control4® Keypads, available in 2, 3, and 6-button configurations, unlock the power of one-touch automation. From lighting and entertainment scenes to complex events involving multiple commands, these Keypads enable effortless control. Custom button labeling helps personalize your Control4® system. Control4 Keypads are also available in a 10-button configuration with an LCD screen for easy list navigation.

Model Number	Control4® Wireless 2-Button Keypad LSZ-3W1	Control4® Wireless 3-Button Keypad KPZ-3B1	Control4® Wireless 6-Button Keypad KPZ-6B1
Programmable Buttons	2	3	6
Button LED Feedback	2 RGB	3 RGB	6 RGB
Power Requirements for 120V keypads	120 VAC +/- 10% 60/50 Hz	120 VAC +/- 10% 60/50 Hz	120 VAC +/- 10% 60/50 Hz
Power Requirements for 240V keypads	220-240 VAC +/- 10% 50/60 Hz	220-240 VAC +/- 10% 50/60 Hz	220-240 VAC +/- 10% 50/60 Hz
Power Consumption	1.4 W - LEDs Off 1.7 W - LEDs On	1.4 W - LEDs Off 1.7 W - LEDs On	1.4 W - LEDs Off 1.7 W - LEDs On
Supports Low-Voltage Installation Option	Yes (using 36 V power supply)	Yes (using 36 V power supply)	Yes (using 36 V power supply)
Multi-Gang Derating	N/A	N/A	N/A
Control Communications	ZigBee (802.15.4) Mesh Networking	ZigBee (802.15.4) Mesh Networking	ZigBee (802.15.4) Mesh Networking
Environmental			
Operational Temperature	32° F - 104° F (0° C - 40° C)	32° F - 104° F (0° C - 40° C)	32° F - 104° F (0° C - 40° C)
Humidity	5% - 95% Non-Condensing	5% - 95% Non-Condensing	5% - 95% Non-Condensing
Storage	-4° F - 158° F (-20° C - 70° C)	-4° F - 158° F (-20° C - 70° C)	-4° F - 158° F (-20° C - 70° C)
Dimensions (H x W x D)	4.6" x 2.75" x 1.6" (117 mm x 70 mm x 41 mm)	4.6" x 2.75" x 1.6" (117 mm x 70 mm x 41 mm)	4.6" x 2.75" x 1.6" (117 mm x 70 mm x 41 mm)
Weight	4.2 oz (139 g)	4.2 oz (139 g)	4.2 oz (139 g)
Available Colors	WH, LA, AL, IV, BR, BL	WH, LA, AL, IV, BR, BL	WH, LA, AL, IV, BR, BL

WH = White, LA = Light Almond, AL = Almond, IV = Ivory, BR = Brown, BL = Black

System Remotes



Control4® System Remote Control SR-150

Designed for use with Control4's On-Screen Navigation, the SR-150 puts the power of total home control in your hand.

Control® System Remote Control SR-250

The SR-250 includes an attractive OLED display with a list Navigator to allow total-home control with or without an on-screen interface.

Model Number	Control4® System Remote SR-150 C4-SR150-Z-B	Control4® System Remote SR-250 C4-SR250-Z-B
Buttons		
Total Buttons	46	47
Quick Access Control Buttons	2	2
Context Sensitive Programmable Buttons	4	4
Transport Control Buttons	8	8
Display		
Display	On-Screen	On-Screen, Backlit OLED
Enclosure		
High-Impact Molded Plastic	Yes	Yes
Textured Finish	Yes	Yes
Communications		
ZigBee (802.15.4)	Yes	Yes
Power Requirements		
Batteries	4 AAA	4 AA
Dimensions		
L x W x D	6.9" x 2.0" x 0.9" (175 mm x 53 mm x 22 mm)	8.3" x 2.1" x 1.1" (190 mm x 55 mm x 27 mm)
Weight (Including Batteries)	5.6 oz (159 g)	8.8 oz (250 g)
System Requirements		
Software	Release 1.6 or later	Release 1.6 or later